

DEPTH RATING	13,200" WITH 4 ½" DRILL PIPE
<b>POWER SYSTEM</b>	
MITSUBISHI ENGINES	2 @ 1300 HP EACH
KATO GENERATORS	2 @ 1020 KW
SCR SYSTEM	1
SIEMENS WITH SCR/VFD HOUSE	1
<b>HOISTING SYSTEM</b>	
DRAW-WORKS	JC40DZ (1000 HP INPUT) BOMCO
DRILL LINE	1 ¼"
AUTO DRILLER	30KW
DSF-40 EDDY BRAKE	1
<b>MAST</b>	
SIZE	145' MAST, 504,000 LBS. RATING
FLOOR BASE	26' X 8.5"
<b>SUBSTRUCTURE</b>	
GRASSHOPPER STYLE	SELF RISING
CLEAR HEIGHT	19'
ROTARY CAPACITY	500,000 LBS
SET BACK CAPACITY	240,000 LBS
<b>BLOCK/HOOK</b>	
BLOCK/HOOK	1 @ 225 TON - BOMCO
<b>CIRCULATING SYSTEM</b>	
<b>PUMPS</b>	
TRIPLEX BOMCO	2 X 1300 HP
PUMP LINERS	6"
MIXING PUMPS	2 @ 6" X 8" CENTRIFUGAL PUMPS
	75 HP ELECTRICAL MOTORS
<b>MUD PITS</b>	
TANK CAPACITY	1147 BBLs
PREMIX TANK	95 BBL
TIP TANK	65 BBL
AGITATORS	10
MUD GAS SEPARATOR	1
<b>SOLIDS EQUIPMENT</b>	
DERRICK SHALE SHAKERS	2
DESANDER	1 @ 75 KW
DESILTER	1 @ 75 KW
CENTRIFUGE	1

<b>WELL CONTROL EQUIPMENT</b>	
<b>BOP'S</b>	11" X 5000 PSI ANNULAR
	11" X 5000 PSI DOUBLE RAM
	11" X 5000 PSI SINGLE RAM
<b>BOP CONTROL</b>	
MANIFOLD SYSTEM	5 STATION
RESERVOIR	200 GAL
PRESSURE PUMPS	2 AIR OPERATED
ELECTRIC DRIVE TRIPLEX PUMP	1
CHOKER MANIFOLD & KILL LINE	5000 PSI
<b>ROTATING SYSTEM</b>	
SWIVEL	225 TON BOMCO
KELLY	5 1/4" SQUARE DRIVE
ROTARY TABLE	27 1/2" ELECTRIC DRIVE
TOP DRIVE (OPTIONAL)	250 TON 500 HP DQ40BC
	29,200 FT LBS CONTINUOUS TORQUE
	44,000 FT-LBS BREAK OUT TORQUE
<b>DRILLING ASSEMBLY</b>	
DRILL PIPE	4 1/2" 16.60 LB/FT-HARD BANDED, XH
DRILL COLLARS	18 @ 6 3/4"
<b>AUXILIARY EQUIPMENT</b>	
WATER TANK	1- 500 BBL
FUEL TANK	1- 500 BBL
	AUTOMATIC DRILLER, VFD
<b>DRILLERS CABIN</b>	
SCREW TYPE AIR COMPRESSORS	2
11,000 LB AIR HOIST	2

**Disclaimer:**

The Company offers the details of this equipment in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the equipment. A buyer should instruct his agents, or his surveyors, to investigate such details as the buyer desires validated. This equipment is offered subject to prior Price, price change, or withdrawal without notice

