

RIG MODEL:	ZJ 30C, MECHANICAL, CARRIER-MOUNTED RIG, RATED DEPTH: 10000FT WITH 4-1/2" DP
HOISTING, ROTARY & PUMPING EQUIPMENT	
DRAW WORKS	MECHANICALLY DRIVEN. LIFTING CAPACITY: 400,000LBS. EQUIPPED WITH AUXILIARY BRAKE, EMERGENCY BRAKE AND INNER CIRCULATION WATER COOLING SYSTEM. - USA CRITERION
MAKE & MODEL	JC28/11,NPMMP FAST LINE TENSION: 61700LBS/28TON
RATED INPUT HORSEPOWER	1060 HP/2100RPM
AUXILIARY BRAKE	YES MODEL: WCB 324DB MAX BRAKE TORQUE: 33900N.M HEAT POWER: 604KW (NEW)
CROWN PROTECTION	YES,INSTALLING AT DRAWWORK,BUMPER INSTALLED AT CROWN.
AUTOMATIC DRILL CONTROL	NO
NUMBER OF DRAW WORKS	1
DRILLING LINE SIZE	1-1/4"
MAX SPEED	450RPM
DRUM DIAMETER, WIDTH	φ 1168 X 267MM
CLUTCH MODEL	ATD330H (NEW)
DEADLINE ANCHOR	MODEL: JZG30,MADE IN NPMP,CHINA
RIG DRIVE AND/OR POWER UNITS	
NUMBER OF ENGINE	2 SETS
MAKER & MODEL OF ENGINES	CAT3408C DITA 530HP/2100RPM (NEW)
TRANSMISSION	MODEL:ALLISION CLBT5961 INPUT POWER : 410KW MAX SPEED: 2500RPM MAX INPUT TORQUE: 2372N.M TRANSFER RATIO:0.67:1, 1:1, 1.35:1, 2.01:1, 2.68:1, 4:1, 5.12:1(BACK)
ENGINE COMBINNER BOX	MODEL:BJX260 MAX INPUT SPEED: 2500RPM MAX INPUT TORQUE: 26000N.M
TORQUE DECREASING BOX	MODEL: JJX140 MAX INPUT SPEED: 2100RPM MAX OUTPUT TORQUE: 1400KN.M

ROTARY BOX TRANSFER BOX	MODEL: ZX140D MAX INPUT SPEED: 2100RPM MAX INPUT TORQUE: 14000N.M CLUTCH: ATD318
MAST - REBUILT IN USA	
MANUFACTURER	NPMP, CHINA; 38M; ZT180, 225T.4.5M*6M
MODEL	JJ18038
HEIGHT	38M(125FT)
MAX LOAD	430200LBS/180TON
MONKEY BOARD CAPACITY	10000FT (4-1/2"DP), PIPE RACKING SYSTEM
MONKEY BOARD ADJUSTING HIGHT	21.2M 22.7M 24.2M
TRAVELLING BLOCK	FIVE (5) SHEAVES GROOVE DIAMETER: 1-1/4" CAPACITY: 403200 LBS/180 TON MOVING SPEED:0.2-1.5M/S MANUFACTURER:NPMP, CHINA; MADE IN 2006.
WIND PROOF	110KM/H(WITH FULL STANDPIPE)
HOOK LOAD CAPACITY	CAPACITY: 403200 LBS/180 TON MANUFACTURER: NPMP, CHINA; MADE IN 2006.
CROWN BLOCK MAKE AND NO. OF SHEAVES AVAILABLE	MODEL: TC180 SHEAVE: 6+1 GROOVE DIAMETER: 1-1/4" CAPACITY: 403200 LBS/180 TON MANUFACTURER: NPMP, CHINA; MADE IN 2006.
HYDRAULIC WINCH	2 SETS, 1- 3 TON (MODEL: JC3B) 1 - 5 TON (MODEL:JC5B)
SUBSTRUCTURE - REBUILT IN USA	
MANUFACTURER, HEIGHT	NPMP - CHINA.
MODEL	ZT180
TYPE	SIX STICK, FOLDAWAY
MAX LOAD CAPACITY	225TON
RIG FLOOR HEIGHT	6M
CLEARANCE FROM UNDERSIDE OF ROTARY BEAMS TO GROUND LEVEL	5.4M
FLOOR SIZE	6 X 7.2 M

SIMULTANEOUS SET BACK /PIPE RACKING CAPACITY	5" DP 144JTS; 7" DC 10JTS SETBACK CAPACITY: 201600 LBS
MUD PUMP - REBUILT IN USA	
NUMBER OF MUD PUMP	2 SETS
MAKE & MODEL	LANZHOU, CHINA; 3NB1000C
POWERED BY (MAX HP)	1000HP
MAXIMUM CONTINOUS SPM	1500RPM
PRESSURE RATING	35MPA
MAX DISCHARGE	601.7 GAL/S
ENGINE MODEL	2 SETS, MODEL: PZ12V 190PZL , POWER:900KW(1200HP), MAX SPEED:1500RPM.
LUBRICATION SYSTEM	AUTO LUBRICATION
COOLING SYSTEM	COOLING PUMP
SUCTION LINE	12"
DISCHARGE LINE	4" STEEL LINE
CHARGE PUMP	YES, 45KW, STIMULTANEOUS RUNNING WITH MUD PUMP
ROTARY TABLE	
MAKE & MODEL	2 SETS NPMP & ZP205, MAXIMUM OPENING: 20-1/2" DRIVE TYPE: MECHANICAL
MAX LOAD	3150KN
KELLY DRIVE BUSHING	HEXAGONAL, FOR KELLY SIZE: 5-1/4', 3-1/2"
MAX SPEED	300RPM
MAX TORQUE	22.5KN.M
SWIVEL/POWER SWIVEL	
A)MAKE AND MODEL	MANUFACTURER: RUSHI, JIANGSU, CHINA MODEL:SL-170, WITH SPINNER, WASHING PIPE:ID 3" CAPACITY:381000LBS/170TON, CONNECTION:6-5/8 REG. MADE:2006
B)ENGINE MODEL OF POWER SWIVEL	NO.
ROTARY HOSES	
NUMBER,SIZE AND RATING	4" OD, 5000PSI,ANTI - FIRE, BOUGHT FROM USA

CONNECTION THREAD MODEL	4" NPT
STANDPIPE	2 SETS, 4"OD, WORKING PRESSURE: 5000PSI.
STANDPIPE MANIFOLD	4" OD, WORKING PRSSSURE: 5000PSI
AIR COMPRESSORES	
NUMBER	2
TYPE	ESC50-10,50HP 1.0MPA MAX DISCHARGE:5M3/M.
DOGHOUSE	
NUMBER,SIZE	1SET,5.70 X 3.00 X 3.0M,WITH AC
BLOWOUT PREVENTERS & WELL CONTROL EQUIPMENT	
BOP:	MODEL:FH28-35,FZ28-70,2FZ28-70 MAX OPENING: 11" WORKING PRESSOR:10000PSI
CHOCK & KILL MANIFORD MODEL,SIZE , RATING	MODEL: JLKGY70/78, OD:4",ID:65MM. WORKING PRESSURE:5000PSI NO OF HYDRAULIC CONTROL VALVE: 2 NO OF MANUAL CONTROL VALVE: 6 NO OF OTHER CONTROL VALVE : 4 RESOLUTION: 20 PSI CHOKER REMOTE CONTROL PANEL WITH TWO PUMPS STROKE COUNTER AND PRESSURE GAUGES FOR DRILL PIPE AND CASING PRESSURE
BOP CONTROL SYSTEM BOP	
BOP	MODEL: FKQ6406G CAPACITY OF RESERVOIR: 343GAL. QUANTITY OF ACCUMULATORS: 16 GALLONS CAPACITY OF EACH: 21GALLONS ACCUMULATOR WORKING PRESSURE: 3000PSI OIL RESERVOIR VOLUME: 168GALLONS
OIL PUMP	ONE TRIPLEX PUMP WORKING PRESSURE: 3000PSI ELECTRICAL FLOWRATE: 46L/M. TWO AIR PUMP WORKING PRESSURE: 3000PSI FLOWRATE:60L X 2/STROKE ONE MANUAL PUMP

REMOTELY OPERATED CHOKE (Y/N?)	YES MODEL: 6406G WORKING PRESSURE:3000 PSI
BOP CONTROL PANELS	INSTALL CLOSE TO THE DRILLER MODEL :6406G, WORKING PRESSURE: 3000PSI
SPOOL	1 - 11" X 10000 PSI, WITH 2 MANUAL VALVE AND TWO HYDRAULIC VALVE
UPPER KELLY COCKS	2 FOR 5-1/4" KELLY, CONNECTION: 6-5/8" REG LH
LOWER KELLY COCKS	2 FOR 5-1/4"KELLY, CONNECTION: NC50
KELLY SUB	FOR 4-1/2"DP
DRILLER'S CONSOLE	TOTAL WEIGHT – RANGE (LBS): 0-2000KN WEIGHT ON BIT – RANGE (LBS): 0-500KN RPM – RANGE: 0-300R/MIN ROTARY TORQUE–RANGE HIGH AND LOW: 0-40KN.M TONG TORQUE - RANGE (FT-LBS): 0-100KN STAND PIPE PRESSURE - RANGE (PSI): 0-35MPA MUD PUMP STROKE RANGE (STK'S): 0-200SPM TOTAL PIT VOLUME INDICATOR - RANGE (BBLs): 0- 100L/S
MUD SOLIDS CONTROL EQUIPMENT	
ACTIVE MUD TANKS	3 - ACTIVE SURFACE VOLUME: 136M ³ BBL REBUILT IN USA
RESERVE MUD TANKS	1 - 35M ³
ADDITIONAL/WATER TANKS	2 - 42M ³ , WITH 10HP ELECTRICAL PUMP REBUILT IN USA
SAND TRAPS	1 - 6M ³ REBUILT IN USA
TRIP TANK	4 M ³ WITH CENTERFUGAL PUMP REBUILT IN USA
SHALE SHAKERS	2 - USA - DERRICK, MADE IN 2006
DE-SANDER (SPECIFICATIONS)	USA - DERRICK MUD CLEANER, MADE IN 2006
DE-SILTER(SPECIFICATIONS)	USA - DERRICK MUD CLEANER, MADE IN 2006
DE-SANDER & DE-SILTER PUMPS	3 - SB1-6*8" 200M3/H,INPUT POWER 45KW,SHAFT POWER 28KW
MUD CENTRIFUGER (SPECIFICATION)	NO

MUD DE-GASSER (SPECIFICATIONS)	2 - ZQJ300 1.6*0.6 3 M ³ /MIN
DE-GASSER PUMP (SPECS)	11KW
POOR BOY DE-GASSER	YQF-6000;DAGANG 3.2M MUD SEAL HEIGHT 6" VENT LINE DIAMETER 1060L/MIN - GAS FLOW RATE AT KILL RATE
MUD AGITATORS	8 - MODEL:2JW15 POWER:15HP
WATER TANK	2 SETS, EACH WITH 10HP ELECTRIC PUMP VOLUME: 42M ³ REBUILT IN USA
CHEMICAL TANK	2M ³ REBUILT IN USA
DRILL PIPE & DRILL COLLARS	
DRILLING PIPE	4-1/2", 224JTS, 2128M; G-105, NC46 USA NEW
HEAVE WEIGHT DRILLING PIPE	USA NEW - 4-1/2", 22JTS, G-105, NC-46
DRILL COLLARS	USA NEW - 6-1/4", 22JTS, NC46, 8", 6JTS,
KELLY	HEXAGONAL 5-1/4", 2JTS, 40FT
RIG FLOOR EQUIPMENTS	
DRILL PIPE SLIPS	4-1/2"
DRILL COLLAR SLIPS	8", 6-1/4"
CASING SLIPS	NO
DRILL PIPE ELEVATORS	2 - DDZ 4-1/2" 150T
CASING ELEVATORS	NO
TUBING ELEVATORS	NO
HYDRAULIC CASING TONGS	NO
POWER TUBING TONGS	2 SETS - XYQ12A
BACK-UP TONG (B-TONGSB)	2 SETS HYDRAULIC, WITH TORQUE INDICATOR
ELEVATOR BAILS	2 SETS 1- DH250, 250T, 3M - 3-3/8"; 1- DH250, 250T, 1.6M - 3-3/8".
MUD BUCKET	YES, FOR 4-1/2" DP
CELLAR PUMP	2 SETS
FLOAT VALVE	FOR 8-3/4" AND 12-1/4" BIT - USA NEW

ELECTRICAL GENERATING	
GENERATORS	2 - TAD1032GE (220KW/50HZ) 1 - TWD740GE (175KW/60HZ) 1 - CUMMINS (175KW/60HZ) 1 - TAD1631GE (400KW/50HZ)
FUEL STORAGE TANKS	2 - 20M3 DIESEL TANK WITH 10HP ELECTRIC PUMP 1 - 1.5M3 MOBILE TANK
ELECTRICAL CONTROL ROOM	1 SET FOR ALL EQUIPMENT OF LOCATION - REBUILT IN USA
TRANSFORMER	110V FOR LOCAL CAMP - USA NEW
LUBE STORAGE TANK	1 SET - 2M3 (INCLUDE 4 CHAMBERS - USA NEW)
CAMP EQUIPMENTS	
DESCRIBE NUMBER, TYPE, OF CAMP.	1 - SINGLE ROOM WITH OFFICES FOR THE RIG MANAGER, 4 - LIVING ROOM FOR PERSONNEL 1 - KITCHEN WITH WATER TANK
TRANSPORTATION	1 - FORD PICKUP, F-150
SAFETY AND FIRE FIGHTING EQUIPMENT	
FIRE EXTINGUISHERS	25 - DRY CHEMICAL EXTINGUISHER 25LBS 4 - CO2 EXTINGUISHER FROM USA
EYEWASH STATION	2 SETS 1 ON RIG FLOOR 1 ON MUD TANK FROM USA
IN-DERRICK SAFETY EQUIPMENT	4 SETS ANTI-FALLING UNIT FROM USA
MISCELLANEOUS	
LOGGING WINCH	1 SET CJ6000F(6000M) MADE IN 2006
SELF-FLOAT SURVEY EQUIPMENT	ONE SET, MADE IN 2006
FORKLIFT	CAPACITY: 4TON

TRUCK WITH CRANE	CARRY CAPACITY: 9 TON CRANE CAPACITY: 4 TON
NOTE: ALL RIG CHAIN HAS CONVERTED TO USA MADE CHAIN.	
FREE SPARE PARTS INCLUDED WITH PURCHASE (Valued at close to \$1 million USD)	
CROWN	BRAND NEW
TRAVELLING BLOCK	BRAND NEW
SWIVEL	BRAND NEW
MAST	REBUILT IN US
SUBSTRUCTURE	REBUILT IN US
MUD TANK	REBUILT IN US
SHALE SHAKER	BOUGHT IN US
MUD CLEANER	BOUGHT IN US
MUD PUMP ENGINES	2 SETS, USED FOR 1 WELL
BOP (WHOLE SET)	BRAND NEW
ROTARY TABLE (SPARE)	BRAND NEW
ROTARY TABLE BEARING SYSTEM	1 SET
KELLY	1 SET
CHAIN	CHANGED TO US MADE
GENERATOR (SPARE)	VOLVO 400KW
TRANSFORMER	MADE IN US
HWDP	22 JOINTS - BRAND NEW, BOUGHT IN US
DRILL COLLAR	8" 6 JOINTS - BRAND NEW, BOUGHT IN US
DRILL COLLAR	6 1/4" 22 JOINTS - BRAND NEW, BOUGHT IN US
DP	4 1/2" 224 JOINTS MADE IN CHINA (ONLY USED 13 JOINTS FOR 1 WELL)

Disclaimer:

The Company offers the details of this equipment in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the equipment. A buyer should instruct his agents, or his surveyors, to investigate such details as the buyer desires validated. This equipment is offered subject to prior Price, price change, or withdrawal without notice.



com