

<b>RIG MODEL:</b>	<b>ZJ 30C,MECHANICAL, CARRIER-MOUNTED RIG, RATED DEPTH: 10000FT WITH 4-1/2" DP</b>
<b>HOISTING, ROTARY &amp; PUMPING EQUIPMENT</b>	
<b>DRAW WORKS</b>	MECHANICALLY DRIVEN. LIFTING CAPACITY: 400,000LBS. EQUIPPED WITH AUXILIARY BRAKE, EMERGENCY BRAKE AND INNER CIRCULATION WATER COOLING SYSTEM. - USA CRITERION
<b>MAKE &amp; MODEL</b>	JC28/11,NPMMP FAST LINE TENSION: 61700LBS/28TON
<b>RATED INPUT HORSEPOWER</b>	1060 HP/2100RPM
<b>AUXILIARY BRAKE</b>	YES MODEL: WCB 324DB MAX BRAKE TORQUE: 33900N.M HEAT POWER: 604KW (NEW)
<b>CROWN PROTECTION</b>	YES,INSTALLING AT DRAWWORK,BUMPER INSTALLED AT CROWN.
<b>AUTOMATIC DRILL CONTROL</b>	NO
<b>NUMBER OF DRAW WORKS</b>	1
<b>DRILLING LINE SIZE</b>	1-1/4"
<b>MAX SPEED</b>	450RPM
<b>DRUM DIAMETER, WIDTH</b>	φ 1168 X 267MM
<b>CLUTCH MODEL</b>	ATD330H (NEW)
<b>DEADLINE ANCHOR</b>	MODEL: JZG30,MADE IN NPMP,CHINA
<b>RIG DRIVE AND/OR POWER UNITS</b>	
<b>NUMBER OF ENGINE</b>	2 SETS
<b>MAKER &amp; MODEL OF ENGINES</b>	CAT3408C DITA 530HP/2100RPM (NEW)
<b>TRANSMISSION</b>	MODEL:ALLISION CLBT5961 INPUT POWER : 410KW MAX SPEED: 2500RPM MAX INPUT TORQUE: 2372N.M TRANSFER RATIO:0.67:1, 1:1, 1.35:1, 2.01:1, 2.68:1, 4:1, 5.12:1(BACK)
<b>ENGINE COMBINNER BOX</b>	MODEL:BJX260 MAX INPUT SPEED: 2500RPM MAX INPUT TORQUE: 26000N.M
<b>TORQUE DECREASING BOX</b>	MODEL: JJX140 MAX INPUT SPEED: 2100RPM MAX OUTPUT TORQUE: 1400KN.M

ROTARY BOX TRANSFER BOX	MODEL: ZX140D MAX INPUT SPEED: 2100RPM MAX INPUT TORQUE: 14000N.M CLUTCH: ATD318
<b>MAST - REBUILT IN USA</b>	
MANUFACTURER	NPMP, CHINA; 38M; ZT180, 225T.4.5M*6M
MODEL	JJ18038
HEIGHT	38M(125FT)
MAX LOAD	430200LBS/180TON
MONKEY BOARD CAPACITY	10000FT (4-1/2"DP), PIPE RACKING SYSTEM
MONKEY BOARD ADJUSTING HIGHT	21.2M 22.7M 24.2M
TRAVELLING BLOCK	FIVE (5) SHEAVES GROOVE DIAMETER: 1-1/4" CAPACITY: 403200 LBS/180 TON MOVING SPEED:0.2-1.5M/S MANUFACTURER: NPMP, CHINA; MADE IN 2006.
WIND PROOF	110KM/H( WITH FULL STANDPIPE)
HOOK LOAD CAPACITY	CAPACITY: 403200 LBS/180 TON MANUFACTURER: NPMP, CHINA; MADE IN 2006.
CROWN BLOCK MAKE AND NO. OF SHEAVES AVAILABLE	MODEL: TC180 SHEAVE: 6+1 GROOVE DIAMETER: 1-1/4" CAPACITY: 403200 LBS/180 TON
HYDRAULIC WINCH	2 SETS, 1- 3 TON (MODEL: JC3B) 1 - 5 TON (MODEL:JC5B)
<b>SUBSTRUCTURE - REBUILT IN USA</b>	
MANUFACTURER, HEIGHT	NPMP, CHINA.
MODEL	ZT180
TYPE	SIX STICK, FOLDAWAY
MAX LOAD CAPACITY	225TON
RIG FLOOR HEIGHT	6M
CLEARANCE FROM UNDERSIDE OF ROTARY BEAMS TO GROUND LEVEL	5.4M
FLOOR SIZE	6 X 7.2 M
SIMULTANEOUS SET BACK /PIPE RACKING CAPACITY	5" DP 144JTS; 7" DC 10JTS SETBACK CAPACITY: 201600 LBS

<b>MUD PUMP - REBUILT IN USA</b>	
NUMBER OF MUD PUMP	2 SETS
MAKE & MODEL	LANZHOU, CHINA; 3NB1000C
POWERED BY (MAX HP)	1000HP
MAXIMUM CONTINUOUS SPM	1500RPM
PRESSURE RATING	35MPA
MAX DISCHARGE	601.7 GAL/S
ENGINE MODEL	2 SETS, MODEL: PZ12V 190PZL , POWER:900KW(1200HP), MAX SPEED:1500RPM.
LUBRICATION SYSTEM	AUTO LUBRICATION
COOLING SYSTEM	COOLING PUMP
SUCTION LINE	12"
DISCHARGE LINE	4" STEEL LINE
CHARGE PUMP	YES, 45KW, STIMULTANEOUS RUNNING WITH MUD PUMP
<b>ROTARY TABLE</b>	
MAKE & MODEL	2 SETS NPMP & ZP205, MAXIMUM OPENING: 27-1/2" DRIVE TYPE: MECHANICAL
MAX LOAD	4500KN
KELLY DRIVE BUSHING	HEXAGONAL, FOR KELLY SIZE: 5-1/4', 3-1/2"
MAX SPEED	300RPM
MAX TORQUE	27.5KN.M
<b>SWIVEL/POWER SWIVEL</b>	
A)MAKE AND MODEL	MANUFACTURE: RUSHI, JIANGSU, CHINA MODEL:SL-170, WITH SPINNER, WASHING PIPE:ID 3" CAPACITY:381000LBS/170TON, CONNECTION:6-5/8 REG. MADE:2006
B)ENGINE MODEL OF POWER SWIVEL	NO.
<b>ROTARY HOSES</b>	
NUMBER,SIZE AND RATING	4" OD, 5000PSI,ANTI - FIRE, BOUGHT FROM USA
CONNECTION THREAD MODEL	4" NPT
STANDPIPE	2 SETS, 4"OD, WORKING PRESSURE: 5000PSI.

STANDPIPE MANIFOLD	4" OD, WORKING PRSSSURE: 5000PSI
<b>AIR COMPRESSORES</b>	
NUMBER	2
TYPE	ESC50-10,50HP 1.0MPA MAX DISCHARGE:5M3/M.
<b>DOGHOUSE</b>	
NUMBER,SIZE	1SET,5.70 X 3.00 X 3.0M,WITH AC
<b>BLOWOUT PREVENTERS &amp; WELL CONTROL EQUIPMENT</b>	
BOP:	MODEL: FH28-35,FZ28-70 ,2FZ28-70 MAX OPENING: 11" WORKING PRESSOR:10000PSI
CHOCK & KILL MANIFORD MODEL,SIZE , RATING	MODEL:JLKGY70/78, OD:4",ID:65MM. WORKING PRESSURE:5000PSI NO OF HYDRAULIC CONTROL VALVE: 2 NO OF MANUAL CONTROL VALVE: 6 NO OF OTHER CONTROL VALVE : 4 RESOLUTION: 20 PSI CHOKE REMOTE CONTROL PANEL WITH TWO PUMPS STROKE COUNTER AND PRESSURE GAUGES FOR DRILL PIPE AND CASING PRESSURE
<b>BOP CONTROL SYSTEM BOP</b>	
BOP	MODEL: FKQ6406G CAPACITY OF RESERVOIR: 343GAL. QUANTITY OF ACCUMULATORS: 16 GALLONS CAPACITY OF EACH: 21GALLONS ACCUMULATOR WORKING PRESSURE: 3000PSI OIL RESERVOIR VOLUME: 168 GALLONS
OIL PUMP	ONE TRIPLEX PUMP WORKING PRESSURE: 3000PSI ELECTRICAL FLOWRATE: 46L/M. TWO AIR PUMP WORKING PRESSURE: 3000PSI FLOWRATE:60L X 2/STROKE ONE MANUAL PUMP
REMOTELY OPERATED CHOKE (Y/N?)	YES MODEL: 6406G WORKING PRESSURE:3000 PSI

BOP CONTROL PANELS	INSTALL CLOSE TO THE DRILLER MODEL :6406G, WORKING PRESSURE: 3000PSI
SPOOL	1 - 11" X 10000 PSI, WITH 2 MANUAL VALVE AND TWO HYDRAULIC VALVE
UPPER KELLY COCKS	2 FOR 5-1/4" KELLY, CONNECTION: 6-5/8" REG LH
LOWER KELLY COCKS	2 FOR 5-1/4" KELLY, CONNECTION: NC50
KELLY SUB	FOR 4-1/2"DP
DRILLER'S CONSOLE	TOTAL WEIGHT – RANGE (LBS): 0---2000KN WEIGHT ON BIT – RANGE (LBS): 0---500KN RPM – RANGE: 0---300R/MIN ROTARY TORQUE–RANGE HIGH AND LOW: 0--- 40KN.M TONG TORQUE - RANGE (FT-LBS): 0---100KN STAND PIPE PRESSURE - RANGE (PSI): 0---35MPA MUD PUMP STROKE RANGE (STK'S): 0---200SPM TOTAL PIT VOLUME INDICATOR - RANGE (BBLs): 0--- 100L/S
<b>MUD SOLIDS CONTROL EQUIPMENT</b>	
ACTIVE MUD TANKS	3 - ACTIVE SURFACE VOLUME: 136M <sup>3</sup> BBL REBUILT IN USA
RESERVE MUD TANKS	1 - 35M <sup>3</sup>
ADDITIONAL/WATER TANKS	2 - 42M <sup>3</sup> , WITH 10HP ELECTRICAL PUMP REBUILT IN USA
SAND TRAPS	1 - 6M <sup>3</sup> REBUILT IN USA
TRIP TANK	4 M <sup>3</sup> WITH CENTERFUGAL PUMP REBUILT IN USA
SHALE SHAKERS	2 - USA - DERRICK, MADE IN 2006
DE-SANDER (SPECIFICATIONS)	USA - DERRICK MUD CLEANER, MADE IN 2006
DE-SILTER(SPECIFICATIONS)	USA - DERRICK MUD CLEANER, MADE IN 2006
DE-SANDER & DE-SILTER PUMPS	3 - SB1-6*8" 200M3/H, INPUT POWER 45KW, SHAFT POWER 28KW
MUD CENTRIFUGER (SPECIFICATION)	NO

MUD DE-GASSER (SPECIFICATIONS)	2 - ZQJ300 1.6*0.6 3 M <sup>3</sup> /MIN
DE-GASSER PUMP (SPECS)	11KW
POOR BOY DE-GASSER	YQF-6000;DAGANG 3.2M MUD SEAL HEIGHT 6" VENT LINE DIAMETER 1060L/MIN - GAS FLOW RATE AT KILL RATE
MUD AGITATORS	8 - MODEL:2JW15 POWER:15HP
WATER TANK	2 SETS, EACH WITH 10HP ELECTRIC PUMP VOLUME: 42M <sup>3</sup> REBUILT IN USA
CHEMICAL TANK	2M <sup>3</sup> REBUILT IN USA
<b>DRILL PIPE &amp; DRILL COLLARS</b>	
DRILLING PIPE	4-1/2", 224JTS, 2128M; G-105, NC46 USA NEW
HEAVE WEIGHT DRILLING PIPE	USA NEW - 4-1/2", 22JTS, G-105, NC-46
DRILL COLLARS	USA NEW - 6-1/4", 22JTS, NC46, 8", 6JTS,
KELLY	HEXAGONAL 5-1/4", 2JTS, 40FT
<b>RIG FLOOR EQUIPMENTS</b>	
DRILL PIPE SLIPS	4-1/2"
DRILL COLLAR SLIPS	8", 6-1/4"
CASING SLIPS	NO
DRILL PIPE ELEVATORS	2 - DDZ 4-1/2" 150T
CASING ELEVATORS	NO
TUBING ELEVATORS	NO
HYDRAULIC CASING TONGS	NO
POWER TUBING TONGS	2 SETS - XYQ12A
BACK-UP TONG (B-TONGSB)	2 SETS HYDRAULIC, WITH TORQUE INDICATOR
ELEVATOR BAILS	2 SETS 1- DH250, 250T, 3M - 3-3/8"; 1- DH250, 250T, 1.6M - 3-3/8".
MUD BUCKET	YES, FOR 4-1/2" DP
CELLAR PUMP	2 SETS
FLOAT VALVE	FOR 8-3/4" AND 12-1/4" BIT - USA NEW

<b>ELECTRICAL GENERATING</b>	
GENERATORS	2 - TAD1032GE (220KW/50HZ) 1 - TWD740GE (175KW/60HZ) 1 - CUMMINS (175KW/60HZ) 1 - TAD1631GE (400KW/50HZ)
FUEL STORAGE TANKS	2 - 20M3 DIESEL TANK WITH 10HP ELECTRIC PUMP 1 - 1.5M3 MOBILE TANK
ELECTRICAL CONTROL ROOM	1 SET FOR ALL EQUIPMENT OF LOCATION - REBUILT IN USA
TRANSFORMER	110V FOR LOCAL CAMP - USA NEW
LUBE STORAGE TANK	1 SET - 2M3 (INCLUDE 4 CHAMBERS - USA NEW)
<b>CAMP EQUIPMENTS</b>	
DESCRIBE NUMBER. TYPE. OF CAMP.	1 - SINGLE ROOM WITH OFFICES FOR THE RIG MANAGER, 4 - LIVING ROOM FOR PERSONNEL 1 - KITCHEN WITH WATER TANK
<b>SAFETY AND FIRE FIGHTING EQUIPMENT</b>	
FIRE EXTINGUISHERS	25 - DRY CHEMICAL EXTINGUISHER 25LBS 4 - CO2 EXTINGUISHER FROM USA
EYEWASH STATION	2 SETS 1 ON RIG FLOOR 1 ON MUD TANK FROM USA
IN-DERRICK SAFETY EQUIPMENT	4 SETS ANTI-FALLING UNIT FROM USA
<b>MISCELLANEOUS</b>	
SELF-FLOAT SURVEY EQUIPMENT	ONE SET, MADE IN 2006
FORKLIFT	CAPACITY: 4TON
<b>NOTE: ALL RIG CHAIN HAS CONVERTED TO USA MADE CHAIN.</b>	

<b>FREE SPARE PARTS INCLUDED WITH PURCHASE (Valued at about \$500,000 USD)</b>	
CROWN	BRAND NEW
TRAVELING BLOCK	BRAND NEW
SWIVEL	BRAND NEW
MAST	REBUILT IN US
SUBSTRUCTURE	REBUILT IN US
MUD TANK	REBUILT IN US
SHALE SHAKER	BOUGHT IN US
MUD CLEANER	BOUGHT IN US
BOP (WHOLE SET)	BRAND NEW
ROTARY TABLE (SPARE)	BRAND NEW
ROTARY TABLE BEARING SYSTEM	1 SET
KELLY	2 SET
CHAIN	CHANGED TO US
GENERATOR	VOLVO - USED ABOUT 30 HOURS
TRANSFORMER	MADE IN US
MUD PUMP ENGINES	2 SETS, NEVER USED
HWDP	21 JOINTS - BRAND NEW, BOUGHT IN US
DRILL COLLAR	8" 5 JOINTS - BRAND NEW, BOUGHT IN US
DRILL COLLAR	6 1/4" 21 JOINTS - BRAND NEW, BOUGHT IN US

**Disclaimer:**

The Company offers the details of this equipment in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the equipment. A buyer should instruct his agents, or his surveyors, to investigate such details as the buyer desires validated. This equipment is offered subject to prior Price, price change, or withdrawal without notice.



com